

# Technical Specifications

<b>Model a700l</b>	<b>PL468AA</b>
<b>Processor &amp; Speed</b>	AMD Sempron S-2800+ 2.0GHz (T)462
<b>Chipset</b>	VIA KM400A
<b>Motherboard</b>	Kelut-GL6E (A7V8X-LA)
<b>RAM</b>	256/3200 MB 400DDR SDRAM (runs@333MHz)
Maximum	2 GB (2x1024MB DDR SDRAM)
Sockets	Two 184-pin DDR DIMMs
Size	128, 256, 512 AND 1024 MB DDR DIMMs
<b>Free DIMM Sockets</b>	One
Pairs Required	No
Type Supported	JEDEC unbuffered DDR SDRAM DIMM specification
<b>Cache</b>	128 KB L1, 256 KB L2 Integrated on Processor module
<b>Hard Drive</b>	40 GB (5400 rpm)
<b>Optical Drive</b>	CD-ROM Drive: 48x maximum speed
Average Random Access	75ms
Transfer Rate	7.2 MB/sec
<b>Diskette Drive</b>	None
<b>Video Graphics</b>	AGP 8X, Integrated
Controller	Integrated w/Via KM400 Chipset
Video Memory	64MB UMA
<b>Network Card</b>	10/100 BaseT, Integrated
<b>1394 Card</b>	IEEE-1394, Integrated
<b>Sound</b>	AC'97, 6 Channel, Integrated on MB
Controller	Realtek ALC658
<b>Chassis</b>	Panther-Lite, 250HV PSU
<b>USB Interface Specification</b>	USB 2.0
<b>External I/O</b> Rear Connectors	4= USB, 1=1394, Serial, Parallel, Line-In, Line-Out; Microphone
<b>External I/O</b> Front Connectors	2= USB, 1=1394, Line In; Microphone, Headphone
<b>Expansion Slots (Total)</b>	3= PCI, 1=AGP
<b>Expansion Slots (FREE)</b>	3= PCI, 1=AGP
<b>Drive Bays (Total)</b>	Two 5.25" external, One 3.5" external, One 3.5" internal
<b>Drive Bays (FREE)</b>	One 5.25" external, One 3.5" external
<b>Keyboard/Mouse</b>	One-touch Enhanced Keyboard, PS/2 Optical scrolling mouse

---

Copyright Hewlett-Packard Co. 1994-2004  
This information is subject to change without notice and is provided "as is" with no warranty.  
Hewlett-Packard shall not be liable for any direct, indirect, special, incidental or consequential damages in connection with the use of this material.